



Champion Vacuum Transport



Utilities Requirements

115vac, 10A, 60Hz

Minimum Product Size

2" W x 2" L

Maximum Product Size

18" W x 18" L

Height

Adjustable, 31-41"
(taller heights available)

Controls

Start, Stop, On/Off, E-Stop, and Variable Speed

Other

Options – Vacuum Blower Assembly,
Infeed Side Guide Assembly, Infeed Nip
-Wheel Assembly

48" Model shown with optional vacuum blower assembly

The CHAMPION Vacuum Transport is designed to transfer a wide variety of paper-type products while maintaining a precise hold of the product via vacuum.

The compact footprint and adjustable height of the Vacuum Transport makes it ideal for use inline with inserters, tabbers, and conveyors or use it offline as a turnkey addressing system. With heat resistant belts and deck top, the Vacuum Transport can also be used for mounting IR dryers to use inline with addressing systems.


The Vacuum Transport is available in 24, 36, 48, and 66-inch lengths.

Simple, easy-to-use controls and minimal tool-free setup adjustments allow for greater uptime thus increasing productivity.

Designed with variable speed control, the Vacuum Transport allows you to control the rate of speed for speed-matching to other equipment.



Used in this system as the base for addressing and print verification



Used in this system as an addressing base



Used in this system as an output verification of pre-printed material



Used in this system as a compact roll in / roll out 2" HP addressing system

Superior-PHS

14414 21st Avenue North
Plymouth, MN 55447

Phone: 763-546-9140
Fax: 763-546-8883

E-mail: info@superior-phs.com
Web: www.superior-phs.com