



Superior Paper Handling Solutions, Inc.

VB-1 Console System

Utilities Requirements

115vac – 20A – 60Hz
(230vac optional upon request)

Product Size

Min. 2"W x 3" L

Max 12"W x 12"L (XM-81)

(other lengths available upon request)

Product Thickness

Min. .003" – Max. .750"

Product Stack Height (XM-81)

20" - Max

(varies with product type & size)

Controls and Interfaces

Full start/stop control including time delay start of the XM-81 feeder.

Variable speed

Easy to use, push button operation

Optional 115vac Dryer interface



The *All-In-One* solution for your addressing, tipping, labeling, and scanning applications.

The high-speed XM-81 product feeder delivers product to the 6' Vacuum Belt Transport and out to the 9-foot Collection Conveyor at speeds up to 500 feet per minute.

The Collection Conveyor can be positioned in-line or right angle (as shown) to fit your production area requirements.

The heavy-duty, robust design provides years of service and maintenance is minimal.

4" Wide center vacuum belt and split chamber design are just some of the standard features on this system.

Superior-PHS

14414 21st Avenue North
Plymouth, MN 55447

Phone: 763-546-9140

Fax: 763-546-8883

E-mail: info@superior-phs.com

Web: www.superior-phs.com



Add stacking capacity to the XM-81 Feeder
with the XM-100 Bulk Product Feeder