



Xtreme XM-2 Friction Feeder



Utilities Requirements

115 – 5A – 60Hz

Product Size

Min. 2"W x 3" L – Max 8.5"W x 11"L

Product Thickness

Min. .003" – Max. .750"

Product Stack Height

20"

Controls and Interfaces

Simple, pushbutton - Cycle, Illuminated Fault, E-Stop, Variable Speed, Trigger Input, and Time-out.

Xtreme Versatile Feeding Solutions provide dependable and consistent performance for operations pursuing greater productivity through automation. The robust design provides years of service and even maintenance, when required is fast and simple to perform, maximizing uptime and productivity.

Built-in versatility provides the flexibility to process the widest variety of material types, sizes, and thicknesses including sheets, forms, plastic cards, greeting & novelty cards, envelopes, folded documents (including open edge), magazines, brochures, and much more, maximizing return on investment.

Simple, easy-to-use controls and minimal tool-free setup adjustments allow for greater uptime, maximizing productivity.

The XTREME XM-2 is ideal for automatic "one-shot" feeding applications including shrink-wrapping and poly-bagging.

The XM-2 is a great value with many standard operating features.

Simple, easy to use controls



Superior-PHS

14414 21st Avenue North
Plymouth, MN 55447

Phone: 763-546-9140

Fax: 763-546-8883

E-mail: info@superior-phs.com

Web: www.superior-phs.com

Compact Footprint...Only 10-inches Wide