

Superior-PHS is the industry leader in simple-to-complex system integrations. We offer the widest range of system components for your application and your budget, including a complete line of Flighted Conveyors. Whatever your requirements, we can offer you the best flighted conveyor solution for integrating with your wrappers, L-sealers, banders, strappers, cartoners, collation & kit fulfillment lines, and much more.

Pictures below show the conveyors with feeders, not included with the conveyors.



Model L-16

This robust, powerful workhorse is the chosen option for nearly any conveying application. This option provides added torque and durability for 24/7 operations.

SPECIFICATIONS:

Features: dual chain, 4-sprocket driven, single lug, flight pins drop vertically (straight down at discharge end), downstream 2-wire system interface, DC Drive

Product Sizes: Min. 3"W x 3" L – Max 16"W x 30"L (other sizes by request) Lug spacing varies with requirements—determined at time of order.

Standard Lengths: 6', 8', 12', or any combination of those lengths up to 200'.

Maximum Speed: Variable speeds up to 100 ft./min

Product Stack Height: 2" standard (optional 4,6 and 8" available)

Deck Height: 31"-35" . Other heights available upon request.

Utilities Requirement: 115vac—10A—60Hz

Options: Indexing Motion Controller, Collection Tray, AC Drive



Model ML-9

The ML-9 conveyor is ideal for low speed, medium duty, indexing applications.

SPECIFICATIONS:

Features: Single Lug, Table Top or Extruded Leg Stand available

Product Sizes: Min. 2"W x 3" L – Max 9.5"W x 10"L (standard lug spacing is 12"...other spacing available by request)

Standard Lengths: 3', 6', 10'

Maximum Speed: Variable speeds up to 30 ft./min. (faster options available)

Product Stack Height: 1/2" standard (other heights available by request)

Deck Height: 31"-35" (with extruded leg stand)

Utilities Requirement: 115vac—10A—60Hz

Options: Product Catch Tray, System Interface Cable