

Xtreme Ultra Series Friction Feeders



The Xtreme Ultra Series delivers state-of-the-art technology, performance, and versatility at the best value on the market.

The **Xtreme XM-20 Ultra** features state-of-the-art technology for use in high-speed batch counting applications and wide format feeding. With belt speeds of 750 ft./min., the XM-20u is the fastest feeder on the market today. Use in batch count, one-shot, or continuous run mode for inline use with shrink-wrapping and poly-bagging equipment, or individual offline batch counting.

The XM-20u features top-line servo motor technology with an intuitive touchscreen PLC, push button controls, and tool-less setup adjustments allowing for greater uptime and maximized productivity. Easily mount to a Superior-PHS mounting stand for use throughout your entire production and fulfillment area.

Get more standard operating features with the XM-20u than any other model including:

- *Electro-Mechanical Double Detect*
- *Vacuum Assist Feeding*
- *Rotating Gate*
- *Pause/Resume Function*



Use the XM-20u for top sheet/backer feeding and batch counting

The advanced features and dependability of the Xtreme Ultra lines make it the peak of feeding technology.

FEEDING SOLUTION FOR

- | | | |
|----------------|---------------|-------------------|
| Stationary | Poly Bags | Z-Folds |
| Photo Paper | Calendars | Signatures |
| Craft paper | Invitations | Bags |
| Magazines | Paper | Collapsed Cartons |
| Folded Docs | Brochures | Plastic Cards |
| Greeting Cards | Die Cuts | Envelopes |
| Coffee Bags | Blister Cards | Direct Mail |
| Holiday Cards | Tri-Folds | Corrugate |
| Chipboard | Forms | Booklets |
| Leaflets | and much more | |

APPLICATIONS & INTEGRATIONS

Feeding Modes:

- Batch count (up to 99,999 pieces)
- One-Shot / On-Demand
- Continuous

Integrate with:

- | | |
|--------------------------|-----------------------|
| Wrappers | Auto L-Bar Sealers |
| Banders | Cartoners |
| Collator & Kitting Lines | Strappers |
| Barcode Readers | Print/Label Systems |
| Inspection Systems | Camera/Vision Systems |
| Bundle Stackers | and much more |

FEATURES & SPECIFICATIONS

Product Sizes*	2"W x 3"L to 20"W x 12"L
Product Thickness	.003" to .750"
Product Stack Height	Up to 20"
Max. Speed	750 ft./min
Footprint Dimensions	30.75"W x 25"L x 23.5"H
Weight	103 lbs. (38.56 kg)
Utilities	230vac - 3A - 60Hz

*Optional lengths up to 27" available.



Wide format batch counting & collating for use with wrappers/sealers, auto L-bars, and more